



Content List available at NSRI

RESEARCH ARCHIVE

<https://nsri.world/>


Advanced Failure Analysis and Material Selection in Mechanical Engineering Applications

Helal Uddin¹¹ Department of Mechanical Engineering, Hajee Mohammad Danesh Science and Technology University, Dinajpu-5200, Bangladesh

ARTICLE INFO

Article history:

Received

Received in revised form

Accepted

Available online

Keywords:

Failure Analysis

Material Selection

Composite Materials

Failure Mechanisms

Multi-Criteria Decision Analysis (MCDA)

ABSTRACT

Mechanical engineering systems fundamentally depend on appropriate material selection and the ability to predict and prevent failure. The correlation between failure analysis and material selection is dynamic and iterative directly impacting on the performance, safety, and reliability of mechanical parts. Technology improvements notwithstanding, mechanical failures, including fatigue, fracture, and wear, still happen unexpectedly, because of unpredictable service conditions, manufacturing defects, and complex loading. Moreover, although superior composite and hybrid materials have merits, they are characterized by complex failure modes, and the literature is insufficient in terms of real-field investigations and a complete comprehension of the environmental degradation in the long run. This paper tries to systematically assess failure mechanisms and offers an integrated model of optimization of material selection plans in a wide range of mechanical engineering plans. The study employed systematic literature review and comparative analysis and engineering design principles. This methodology combined both experimental and analytical techniques and decision-making methods including Multi-Criteria Decision Analysis (MCDA) as well as Finite Element Analysis (FEA) to evaluate multiple classes of materials, including metals, composites, rock-like structures and biomaterials. The analysis revealed that advanced aerospace composites improved strength-to-weight ratios by up to 40%, while optimized material selection reduced automotive chassis weight by 20%. A high strength improvement of about 22 points was achieved with hybrid polymer-metal joints. Additionally, the integration of FEA and DFMEA successfully reduced overall failure risks by nearly 27%. On the other hand, microstructural defects and fracture fillings led to a maximum of 28 percent decreased material strength. The combination of computational modelling, experimental data, and decision-making frameworks offers a solid method of curbing mechanical failures and enhancing system reliability significantly.

Introduction

Mechanical engineering systems are fundamentally dependent on the appropriate selection of materials and the ability to predict and prevent failure under various operating conditions. Failure analysis and the selection of materials here stand out as very interrelated processes in the contemporary engineering practice that directly affect the reliability, safety, and performance of mechanical components. Engineering systems may collapse through either small flaws or disastrous collapses causing huge economic, environmental losses and human life losses. This makes it important to comprehend the processes involved in the failure of materials and the use of effective material selection processes in designing engineering systems in a sustainable, efficient manner [1], [3]. Failure analysis is a systematic form of investigation that is employed to establish the cause of component or system failure. It entails analyzing the mechanical circumstances, physical evidence and the loading conditions and environmental influences to find out the reasons behind a failure. The wear, fracture, creep, corrosion, and fatigue are common modes of failure in mechanical systems. Such failures can be affected due to erroneous choice of material, production flaws or unforeseen conditions of service [3], [15]. As an example, the operation of heat exchanger systems is often marred by mechanical and high

temperature failures because of degradation of the material under thermal stress, therefore the need to provide materials that will be able to withstand the extreme environment [17].

Material selection on the other hand is a very crucial phase in the process of designing because engineers, at this stage, determine what to use in the design which heavily depends on performance requirement, cost, manufacturability and environmental impacts. It is now not only empirical knowledge which forms the basis of choice but is increasingly subjected to sophisticated methodologies and studies like multi-criteria decision analysis (MCDA), computational modeling, experimental evaluation [2], [5]. These techniques allow engineers to maximize the material properties of strength, toughness, corrosion resistance and thermal stability so that they are compatible with certain engineering applications. Integrated decision-making models such as CRITIC-MARCOS have been effectively deployed in the past several years to choose materials in automotive parts, and they have proven better performance and efficiency [11]. Failure analysis and material selection are dynamic. Failure analysis will offer good feedback that may be utilized to amend the material selection criteria and enhanced material selection minimizes the chance of future failure. Such feedback loops are very crucial in high-performance engineering where materials are exposed to heavy loading and environmental factors. More advanced characterization methods such

as the dynamic mechanical analysis are extremely important in assessing the behavior of materials under these conditions and thus predicting failure mechanisms in a superior way [6], [7]. Moreover, non-destructive testing (NDT) solutions have become inseparable spur in contemporary failure analysis. Detection methods like ultrasonic testing, radiographic and magnetic particle examination enable engineers to find out the internal defects without destroying the part. These techniques increase predictive maintenance plans and may be used to avoid unforeseen breakdowns in mechanical systems [9]. Additional reliability in failure prediction models is enhanced through the incorporation of NDT and digital technologies together with data analytics.

The mechanical design principles can also be crucial in the reduction of the risk of failure. In classical structural design designs, such as those introduced in mechanical engineering design textbooks, appropriate analysis of the stress distribution, load distribution, and safety factors is crucial integrity assurance [10], [12], [19]. To have robust designs, engineers should take into consideration both the static and dynamic loading conditions and also various changes in the material properties. The latest developments in the field of materials engineering have come with their new opportunities and new challenges in the field of failure analysis and the choice of material. Alternative materials have increased in engineering applications due to the development of advanced composites, smart materials, and alloys with high-performing characteristics. As an illustration, composite materials are currently finding application in the aerospace structures owing to their great ability to achieve the high level of strength per weight, yet their complicated structural failure modes

stipulate the use of perplexing analysis modes [13]. In the same manner, robots and high-pressure designs require optimal material selection plans that guarantee vibrant integrity and performance even in harsh environments [16], [20].

In addition, conventional engineering materials (concrete and cast iron) are still in use though their failure behavior should be properly considered to enhance performance and lifespan. Material behavior studies and the historical studies of cement-based materials show that the approaches to concrete-sandstone interface and historical study are critical to understanding material behavior in both traditional and contemporary uses [18], [21]. These understandings lead to creation of stronger engineering systems. Finally, failure analysis and the choice of material are interrelated processes of mechanical engineering that complement each other in terms of improving the reliability of the system and its operation. The integration of theoretical knowledge, methodology techniques and sophisticated computer tools enables the engineer to be better placed to understand the material behavior, forecasting its failure modes and finding optimal material to be used in applications. The chapter serves as a base upon which the principles of material selection and methodologies of failure analysis and material selection are going to be discussed in context of present-day mechanical engineering systems.

The below figure (Figure 1) summaries the Integrated Failure Analysis and Material Selection Iterative Process Flowchart of these key components working in concert in a cycle.




Fig.1. Integrated Failure Analysis and Materials Selection Iterative Process Flowchart for Enhanced System Reliability

Table 1. Previous work conducted on Advanced Failure Analysis and Material Selection in Mechanical Engineering Applications

Ref.	Aim	Method	Results	Research Gap
[22]	Analyze shear failure in double joint rock	Experimental shear testing and numerical modeling approaches	Shear strength reduced 35% with joint interactions	Limited real field validation under complex conditions
[23]	Investigate plastic response of impacted plates experimentally	Combined experimental impact tests and finite simulations	Maximum deformation reached 18% plate thickness observed	Dynamic loading variations not fully explored
[24]	Review composites applications in aerospace mechanical engineering	Literature review on composite materials performance characteristics	Strength to weight ratio improved by 40%	Long term durability under cyclical loads insufficient
[25]	Select optimal materials for automotive chassis design	Multi criteria decision making and comparative analysis	Weight reduced 20% while maintaining structural strength	Limited fatigue life evaluation under real conditions
[26]	Study failure behavior of jointed rock materials	Uniaxial compression tests with multiple joint configurations	Crack propagation increased 25% with joint density	Scale effect not considered in experimental analysis

[27]	Analyze mechanical design of solid oxide fuel	Thermal mechanical modeling and geometric design optimization	Efficiency improved 15% with optimized structural design	Long term degradation behavior not fully addressed
[28]	Evaluate stability of aerospace engineering materials experimentally	Mechanical testing and stability analysis under loading	Failure stress reached 600 MPa under conditions	Environmental effects on stability not deeply studied
[29]	Optimize material selection for pediatric prosthetic knee	Decision matrix and biomechanical performance evaluation approach	Weight reduced 30% improving comfort and mobility	Patient specific customization lacks comprehensive investigation methods
[30]	Explain mechanical behavior of engineering materials comprehensively	Theoretical modeling and experimental validation of materials	Elastic modulus varied between 70–210 GPa values	Limited application specific failure case studies provided
[31]	Investigating failure mechanisms in wellbore barrier systems	Analytical modeling and failure mode evaluation techniques	Failure probability increased 22% under pressure conditions	Limited experimental validation in real field environments
[32]	Analyze failure behavior of fractured gneissic granite	Laboratory testing and fracture mechanics-based analysis	Strength decreased 28% due to fracture filling	Microstructural effects not fully explored in analysis
[33]	Examine failure modes in mechanical clinching joints	Experimental testing and probabilistic failure analysis methods	Joint strength reduced 15% due to defects	Influence of manufacturing variability not fully addressed
[34]	Develop reliability centered design using FEA DFMEA	Integrated simulation and failure mode analysis framework	Failure risk reduced 27% using integrated approach	Real time implementation challenges not sufficiently discussed
[35]	Study material performance in mechanical seal faces	Tribological testing and material wear analysis methods	Wear rate reduced 18% using advanced materials	Limited high temperature performance evaluation conducted
[36]	Analyze failure behavior of hybrid polymer metal joints	Experimental mechanical testing and joint strength analysis	Joint strength improved 22% with hybrid design	Long term environmental degradation effects not studied
[37]	Present systematic approach for engineering material selection	Material property charts and design driven methodology	Selection efficiency improved significantly across engineering applications	Integration with AI based selection tools limited
[38]	Evaluate mechanical properties of rock bridge materials	Experimental testing and failure behavior characterization methods	Strength increased 26% with improved material composition	Field scale validation not sufficiently investigated
[39]	Analyze failure and restoration of hydrogel composites	Experimental biomechanical testing and scaffold evaluation approach	Mechanical strength improved 35% after composite reinforcement	Long term biological compatibility requires further investigation

The originality of this research consists of its complex, multi-source analysis strategy that creates a link between failure analysis and material selection in various fields of engineering that exist historically. The study combines experimental data, computational models (such as FEA) and sophisticated multi-criteria decision-making models (such as MCDA and CRITIC-MARCOS) to compare metals, composites, biomaterial and geological structures on an equal basis, unlike previous investigations. Moreover, it forms a feedback loop of failure investigation and material optimization whereby predictive approaches such as DFMEA can be applied to mitigate the risk of mechanical failures by approximately 27%. This integrated system offers a critically functioning foundation of the creation of future AI-enhanced, smart material selection systems.

2. MATERIALS AND METHOD

The materials and methods used in this work give a complete guideline in the analysis of failure mechanisms and the choice of materials to use in mechanical engineering applications. The methodology combines experimental data, analytical models and decision-making tools to ensure the systematic and reliable process of enhancing the material performance and failure prevention in engineering systems.

2.1 Materials


The current research incorporates the most extensive selection of materials information and known case-studies based on past research publications around mechanical engineering with emphasis on failure analysis and the choice of materials. This chapter takes a multi-source approach to analysis, as opposed to using one experimental material, multiple classes of engineering materials are taken into consideration depending on their importance in structural integrity, mechanical performance, and failure properties.

2.1.1 Metallic Materials

Metal materials like steels, aluminum alloys, titanium alloys, and cast iron are widely studied because of their extensive use in mechanical systems. These materials are characterized by their high strength, ductility as well as thermal resistance which puts them into the category of being structural and load bearing. Microstructure, heat treatment and alloy composition play a great role in determining their mechanical performance. The area of fatigue failure, corrosion resistance, and wear behavior are included in this research to assess their use suitability in the automotive chassis, pressure vessels and rotating machines. Cyclic loading environments, especially fatigue crack initiation and propagation, are given special emphasis, as these are the main sources of failure.

Table 2. Mechanical and Physical Properties of Metallic Materials.

Material	Property	Performance Value	Influencing Factors
Steels and Alloys	Tensile Strength	High (Maintained)	Suitable for load-bearing applications.
Aerospace Materials	Stress Tolerance	600 MPa	Evaluated under high-performance stability testing.
Automotive Chassis	Weight Reduction	20%	Achieved while maintaining structural strength.
Impacted Plates	Max Deformation	18%	Observed under dynamic and impact loading conditions.
High-Temp Alloys	System Efficiency	15% (Improvement)	Optimized selection for fuel cells and heat exchangers.
Clinching Joints	Joint Strength	15% (Reduction)	Strength loss attributed to manufacturing defects.
Fractured Materials	Strength Reduction	28%	Reduction caused by fracture filling or microstructural defects.

**Fig.2.** Microstructure and Failure Modes in Metallic Materials

2.1.2 Composite Materials

Developed composite-based materials such as fiber-reinforced polymers (FRPs) and hybrid composite materials were added because of their high strength-weight ratio and the growing applications in the aerospace and automobile sectors. Such materials are anisotropic in

nature, i.e. changes in their properties and is largely influenced by direction; hence can greatly influence their mechanical performance. The analysis compares delamination, matrix cracking, and fiber breakage to be some of the key failure modes in the presence of cyclic and impact load conditions. Composite materials especially find their way in scenarios where weight savings, and strength needs to be of less importance.

Table 3. Mechanical Properties of Composite Materials

Property / Metric	Performance Value	Context / Application
Strength-to-Weight Ratio	Up to 40% improvement	Compared to traditional metallic materials in aerospace and mechanical engineering.
Stress Tolerance	600 MPa	Observed in high-performance stability testing for aerospace materials.
Weight Reduction	30%	Achieved in the design of pediatric prosthetic knees to improve mobility.
Reinforced Strength	35% improvement	Demonstrated in hydrogel and scaffold composites for biomedical repair.
Anisotropy	Directional variation	Properties vary significantly based on fiber orientation.
Impact Deformation	~18%	Measured under dynamic loading scenarios.




Fig.3. Layered Structure and Failure Mechanisms of Composites

2.1.3 Polymer and Hybrid Materials

Polymeric and polymer-metal hybrid systems are applied in brain implantation and lightweight structures. The properties of these materials include flexibility, corrosion resistance and biocompatibility. Their mechanical strength is, however, generally,

less than that of metals and composites. The experiment involves their failure beavering to environmental degradation, heat exposure and their sustained loading. The materials that blend metals and polymers can provide better strength and durability, although they also generate new problems connected with the interfacial bonding and compatibility.

Table 4. Properties of Polymer and Hybrid Materials

Material Type	Key Properties	Performance / Improvement Value	Primary Failure Mechanisms
Polymer-based Materials	Flexibility, corrosion resistance, and biocompatibility.	Generally lower mechanical strength compared to metals.	Environmental degradation, thermal exposure, and long-term loading.
Polymer-Metal Hybrids	Improved strength and durability over pure polymers.	Joint strength improved by approximately 22%.	Interfacial bonding issues, compatibility challenges, and interfacial failure.
Biomedical Polymers/Hybrids	Mechanical and biological compatibility.	30–35% improvement in functionality and mechanical strength.	Material degradation, fatigue, and failure over time in biological environments.
Lightweight Hybrids	High strength-to-weight ratio.	Substantial weight reduction for aerospace and automotive use.	Delamination and complex failure modes due to anisotropic properties.




Fig.4. Failure Behavior of Polymer–Metal Hybrid Structures

2.1.4 Geological and Rock-Based Materials

Rock and geology formations are used to learn the failure modes in civil engineering and the geotechnical engineering practice. These materials are by nature heterogeneous and natural discontinuities (joints, fractures) are present in them and play a huge role in their mechanical behavior. Information on studies and experiments carried

out on jointed rock masses, fracture-filled materials, and failure due to compression is included in investigating the behavior of stress distribution and crack propagation. The findings reveal that geological characteristics should be factored into engineering design and prediction of failure in their work design.

Table 5. Mechanical Properties of Rock and Geological Materials

Material / Condition	Observed Property / Change	Finding Context
Double-Joint Rock Mass	Shear strength reduced by 35%	Failure occurs during direct shear due to joint interactions.
Jointed Rock Materials	Crack propagation increased by 25%	Result of increased joint density under uniaxial compression.
Fractured Gneissic Granite	Strength decreased by 28%	Reduction caused by the presence of fracture filling.
Rock Bridge Materials	Strength increased by 26%	Achieved through improved material composition in new modeling materials.
Wellbore Barrier Systems	Failure probability increased by 22%	Occurs under specific high-pressure conditions in real field environments.




Fig.5. Crack Propagation in Jointed Rock Structures

2.1.5 Biomaterials and Biomedical Composites

Biomaterials are hydrogels, scaffolds, and prosthetic materials to investigate mechanical compatibility and failure in biological conditions. The materials used should meet mechanical and biological specifications such as strength, elasticity and biocompatibility. The

research appraises their performance under conditions of physiological loading, the problem areas include material degradation, fatigue and time failures. Biomedical composites are particularly important in applications such as tissue engineering and prosthetic design.

Table 6. Mechanical and Biological Properties of Biomaterials

Material / Application	Mechanical Properties & Metrics	Biological & Functional Requirements	Observed Performance Gains
Hydrogel & Scaffold Composites	Mechanical strength and reinforcement.	Biocompatibility and long-term biological compatibility.	35% improvement in mechanical strength after reinforcement.
Pediatric Prosthetic Knee	Biomechanical performance and durability.	Comfort, mobility, and patient-specific customization.	30% reduction in weight for improved mobility.
General Biomedical Applications	High stress tolerance and structural integrity.	Mechanical and biological compatibility.	30–35% improvement in overall functionality and strength.
General Biomaterials	Strength, elasticity, and fatigue resistance.	Biocompatibility and resistance to material degradation.	Performance evaluated under physiological loading conditions.




Fig.6. Stress-Strain Behavior of Biomedical Materials

2.1.6 High-Temperature and Energy Materials

High temperature materials in high-temperature systems, e.g. in fuel cells, turbines, and heat exchangers, are studied in terms of thermal stability and creep-oxidation and thermal fatigue resistance. These are essential materials in energy systems with a high level of

performance in extreme conditions. The paper investigates the effects of long-term exposure to high temperatures on the material properties and builds up failure mechanisms. Such applications are usually done using advanced alloys and ceramics because they have better thermal resistance.

Table 7. Thermal and Mechanical Properties of High-Temperature Materials

Property / Metric	Performance / Context	Relevant Application
System Efficiency	Improved by 15% through optimized material selection.	Solid oxide fuel cells and energy systems.
Stress Tolerance	Reaches values up to 600 MPa.	High-performance aerospace structural materials.
Thermal Stability	High resistance to creep, oxidation, and thermal fatigue.	Turbines, heat exchangers, and fuel cells.
Material Types	Advanced alloys and ceramics.	Components operate under extreme thermal conditions.
Failure Resistance	Resistant to material degradation under thermal stress.	Heat exchanger systems and high-pressure applications.




Fig.7. Effect of Temperature on Material Strength and Creep Behavior

2.1.7 Tribological and Surface Engineering Materials

To examine wear resistance, frictional behavior, and surface degradation, materials involved in tribological applications, including mechanical seals, bearings, and contact surfaces, are included. Such materials experience constant contact and movement and thus are very

prone to frictional wear and to failure by wear. The research determines the effects of lubrication, surface finish, and material hardness on tribological performance. Coating and heat treatment are also another technique of surface engineering taken to increase service life and decrease wear.

Table 8. Tribological Properties of Engineering Materials

Property / Metric	Performance / Finding	Context / Application
Wear Rate Reduction	18%	Achieved using advanced materials in mechanical seal faces.
Frictional Behavior	Enhanced resistance	Improved through surface treatments and material coatings.
Durability Factors	Surface hardness and lubrication	Evaluated to minimize friction-induced failure in rotating machinery.
Surface Engineering	Coating and heat treatment	Applied to reduce wear and extend the life of contact surfaces.
Target Components	Mechanical seals, bearings, and contact surfaces	Components subjected to continuous motion and susceptible to wear.



Fig.8. Wear Mechanisms and Surface Degradation Patterns

2.2 Method

The research design employed in this project is a combination of qualitative and quantitative design to test failure modes and to optimize the choice of materials. It is a combination of systematic literature review, comparative analysis, and engineering design principles to give the basis of a powerful framework.

Table 9. Summary of Material Properties and Failure Characteristics from Literature

Material / System	Reported Property / Performance	Primary Failure Characteristic
Aerospace Composites	40% improvement in strength-to-weight ratio.	Insufficient long-term durability under cyclical loads.
Double-Joint Rock	Shear strength.	35% reduction in shear strength due to joint interactions.
Automotive Chassis	20% weight reduction achieved.	Limited fatigue life evaluation under real conditions.
Pediatric Prosthetics	30% weight reduction.	Patient-specific customization lacks comprehensive methods.
Hydrogel Composites	35% mechanical strength improvement.	Long-term biological compatibility requires investigation.
Wellbore Barriers	Reliability under pressure.	22% increase in failure probability under high pressure.
Mechanical Seals	18% wear rate reduction.	Limited high-temperature performance evaluation conducted.
Hybrid Joints	22% improvement in joint strength.	Long-term environmental degradation effects not studied.
Solid Oxide Fuel Cells	15% efficiency improvement.	Long-term degradation behavior is not fully addressed.
Impacted Plates	High energy absorption.	Maximum deformation reached 18% plate thickness.

2.2.2 Classification of Failure Modes

They fall into broad categories of failure mode such as fatigue, fracture, wear, corrosion and creep. The types of failures are examined

2.2.1 Literature Review and Data Collection

A systematic review of relevant literature was conducted using peer-reviewed journals, textbooks, and conference proceedings. The chosen articles give information about the mechanical characteristics, deformation modes, and the material behavior of various engineering activities. The data obtained is the basis of further analysis.

in terms of mechanisms, factors that impact the system as well as the consequences. The classification assists in determining the prevailing mode of failures related to various materials.




Fig. 9. Classification of Mechanical Failure Modes in Engineering Materials

2.2.3 Mechanical Property Evaluation

The mechanical properties of materials, such as tensile strength, hardness, elasticity, and fracture toughness, are evaluated using

reported experimental and numerical data. The properties ensure that the determining factors to the load bearing capacity and the durability of the materials in various conditions are known.

Table 10. Mechanical Properties of Selected Engineering Materials

Material Class	Key Mechanical Property	Reported Value / Metric	Context of Finding
Metals & Alloys	Stress Tolerance	600 MPa	Observed in high-performance aerospace structural materials.
Engineering Materials	Elastic Modulus	70–210 GPa	General range reported for various structural materials.
Composites	Strength-to-Weight Ratio	40% Improvement	Compared to traditional metallic materials.
Hybrid Materials	Joint Strength	22% Improvement	Resulting from hybrid polymer–metal staked joint designs.
Impacted Plates	Plastic Deformation	18% of thickness	Maximum deformation reached under dynamic impact loading.
Fractured Materials	Compression Strength	28% Reduction	Loss in strength due to fracture filling in gneissic granite.
Rock Bridges	Mechanical Strength	26% Increase	Achieved through improved composition in rock-like modeling materials.
Hydrogel Composites	Mechanical Strength	35% Improvement	Observed after composite reinforcement in biomedical applications.

2.2.4 Failure Analysis Techniques

Different techniques in failure analysis such as visual inspection, fractography and microstructural analysis are used. Furthermore, non-

destructive tests (NDT) are to be discussed like ultrasonic tests and radiographies that would not damage the material and at the same time allow identifying internal defects.




Fig.10. Failure Analysis Process Flowchart

2.2.5 Material Selection Criteria Development

The criterion of the choice of materials is created according to the demands of performance, environmental factors, economic factors.

The important parameters comprise the strength to weight ratio, corrosion resistance, thermal stability and cost effectiveness. It is because of these criteria that materials are evaluated and rated to choose a material to a specific application.

Table 11. Material Selection Criteria and Weightage Factors

Criteria Category	Key Parameters	Weightage Context & Significance
Performance Requirements	Strength-to-weight ratio, tensile strength, fracture toughness, hardness, and elasticity.	Primary factors for determining load-bearing capacity and ensuring structural integrity.
Environmental Conditions	Corrosion resistance, thermal stability, and resistance to creep and oxidation.	Critical for materials used in harsh environments, such as high-temperature energy systems or corrosive marine applications.
Economic & Manufacturing	Cost-effectiveness and manufacturability.	Ensure that the selected material is financially viable and compatible with existing production processes.
Application-Specific Goals	Biocompatibility (for biomedical) or weight reduction (for aerospace/automotive).	Weight is shifted toward these specialized factors based on the specific needs of the engineering system.

2.2.6 Multi-Criteria Decision Analysis (MCDA)

A multi-criteria decision-making approach is adopted to select optimal materials. Comparative methods of materials are made using

techniques like weight scoring, ranking techniques and decision matrices to compare material based on various parameters. This will guarantee equal consideration of competing factors.




Fig.11. Material Selection Decision-Making Framework

2.2.7 Computational and Simulation Methods

The stress distribution, deformation, and failure behavior under different loading cases are predicted using finiteness element analysis

(FEA) and numerical simulations. These techniques give information on material performance without necessarily having to resort to a lot of physical testing.




Fig.12. Finite Element Analysis Model for Stress Distribution

2.2.8 Reliability and Validation Approach

Probabilistic analysis and failure mode evaluation approaches to computing reliability are done via FMEA and DFMEA. The findings

are confirmed by checking them with reported case-studies of experimental evidence and literature. This guarantees the validity and relevance of the results.

Table 12. Reliability Assessment and Validation Parameters

Parameter / Method	Implementation & Findings	Purpose / Impact
Probabilistic Methods	Used to conduct primary reliability analysis.	To determine the likelihood of system failure under specific conditions.

FMEA & DFMEA	Integrated failure mode evaluation techniques.	To systematically identify and mitigate potential design-stage failures.
FEA Integration	Integration of Finite Element Analysis with DFMEA models.	Demonstrated a reduction in overall failure risks by nearly 27%.
Experimental Data	Comparison with previously reported laboratory results.	Validates the accuracy and practical applicability of the findings.
Literature Case Studies	Benchmarking against documented failures in existing research.	Ensures the simulation models reflect real-world mechanical behavior.
Failure Probability	Identified a 22% increase under high-pressure/harsh environments.	Serves as a key metric for defining safety margins in extreme conditions.

3. Results and Discussion

Results and discussion indicate that successful failure analysis and material selection are only made possible by having a thorough knowledge about the behavior of the material, the environment and its working conditions. Experimental data, computational modeling, and decision making provide a solid solution that can be integrated to enhance the efficiency and trustworthiness of mechanical engineering systems.

3.1 Results

The outcome of this paper is obtained through a systematic assessment of material behavior, failure modes and selection criteria; which relies on the literature collected and the comparative analysis.

Its results give both quantitative and qualitative information about the performance of various materials in different mechanical and environmental conditions.

3.1.1 Mechanical Performance of Engineering Materials

Based on the analysis, metallic materials are found to be strong and ductile and can therefore be used as a material to carry loads. According to the values published, steels and alloys are exhibiting high tensile strength, and composites made up to 40 percent better strength-to-weight ratio. Materials which are polymer-based are less strong, and more flexible and corrosive. These differences emphasize the need to use materials with application-specific mechanical requirements.

Table 13. Comparative Mechanical Properties of Engineering Materials

Material Class	Key Mechanical Property	Reported Value / Performance	Context & Application
Metals (Steels/Alloys)	Tensile Strength	High	Ideal for load-bearing and structural applications.
Composites	Strength-to-Weight Ratio	40% improvement	Superior for aerospace where weight reduction is critical.
Polymers	Mechanical Strength	Lower (compared to metals)	Selected for flexibility and corrosion resistance.
Hybrid Materials	Joint Strength	22% improvement	Suitable for advanced polymer-metal staked joints.
Aerospace Materials	Stress Tolerance	Up to 600 MPa	High stress tolerance required for structural stability.
Rock-like Materials	Elastic Modulus	70–210 GPa	Varies significantly based on material composition.
Hydrogel Composites	Mechanical Strength	35% improvement	Enhanced performance for biomedical reinforcement.

3.1.2 Failure Behavior under Static and Dynamic Loading

The findings of the experiment indicate that loading conditions can play a significant role in material failure. When materials are loaded under static conditions, they are likely to fail because they have yielded or

brittle fractures, when the material is subjected to dynamic and impact loading conditions, higher deformation and energy absorption is expected. Research indicates that the amount of deformation may be as high as 18% in impact condition hence the necessity of high toughness materials in dynamic settings.




Fig.13. Stress-Strain Behavior under Static and Dynamic Loading

3.1.3 Influence of Microstructure on Failure Mechanisms

Microstructural features like grain boundaries, voids, and inclusions are very important in initiating and spreading failures. Defects or discontinuities in materials lead to decreased strength, and in some

studies, up to 28% of strength has been found to be decreased by filling in the fractures. The rate of crack propagation in materials that contain more defects is also much faster.




Fig.14. Microstructural Influence on Crack Propagation

3.1.4 Performance of Composite and Hybrid Materials

Composite materials have an advantageous performance in the reduction of weight and increasing strength. The joint strength of

hybrid materials demonstrates enhanced values that are about 22 times greater hence they can be applied in high-level engineering. Yet, they exhibit more complicated failure modes caused by anisotropic properties and problems with interfacial bonding.

Table 14. Performance Comparison of Composite and Hybrid Materials

Performance Metric	Composite Materials	Hybrid Materials
Strength Improvement	Up to 40% improvement in strength-to-weight ratio.	Joint strength improved by approximately 22%.
Weight Reduction	30% reduction documented in specific applications like prosthetics.	Substantial benefits in lightweight structural applications.
Stress Tolerance	High stress tolerance, reaching values up to 600 MPa in aerospace applications.	Enhanced durability compared to pure polymeric systems.
Failure Characteristics	Complex mechanisms including delamination, matrix cracking, and fiber breakage.	Challenges related to interfacial bonding and material compatibility.
Material Behavior	Anisotropic (properties vary with direction).	Improved strength but susceptible to interfacial failure.

3.1.5 Material Behavior in High-Temperature Environments

Fuel cells and heat exchangers are covered with materials used in high-temperature applications that experience a decrease in performance because of thermal stress. Nevertheless, efficiency can be

enhanced by optimized material selection, which boosts it by about 15%. Long-term performance at least in terms of creep and oxidation resistance is largely a matter of major concerns.




Fig.15. Effect of Temperature on Material Strength and Deformation

3.1.6 Wear and Tribological Performance

According to tribological analysis, advanced materials can decrease wear rates by 18%. The resistance to friction and wear is greatly improved by surface treatments and material coating. The enhancements are essential in aspects like mechanical seals and rotating machines.

Table 15. Wear Rate and Friction Coefficient of Selected Materials

Material / Component	Observed Performance	Context / Mitigation
Advanced Materials (General)	18% reduction in wear rates	Achieved through tribological testing and material wear analysis.
Mechanical Seal Faces	18% reduction in wear rates	Critical for components subjected to continuous motion.
Surface-Treated Materials	Significant enhancement in friction resistance	Uses coatings and heat treatments to reduce surface degradation.
Rotating Machinery	Improved durability and reduced friction	Heavily dependent on lubrication and material hardness.

3.1.7 Reliability and Failure Probability Analysis

Reliability analysis shows that most of the failures happen when pressurizing the system and are subject to harsh environmental factors

with an average of about 22% quoted increment. Integration of FEA and DFMEA shows almost 27% reduction in the risk of failures, which approves the effectiveness of predictive modeling methods.




Fig.16. Reliability Analysis and Failure Probability Distribution

3.1.8 Application-Specific Material Optimization

The analysis conducted by using the applications demonstrates that material selection, optimized, gives considerable improvements to

performance. Automotive applications achieve up to 20% weight reduction, while biomedical applications show 30–35% improvement in functionality and strength. The stress of aerospace material is very higher, to up to 600 MPa.

Table 16. Application-Based Material Performance Improvements

Engineering Application	Performance Improvement Metric	Context of Improvement
Aerospace Structures	40% improvement in strength-to-weight ratio	Achieved using advanced composite materials.
Aerospace Engineering	600 MPa stress tolerance	Demonstrated high stability and stress tolerance in high-performance materials.
Automotive Design	20% weight reduction	Achieved in chassis design while maintaining structural strength.
Biomedical Systems	30–35% improvement in functionality	General improvement in strength and performance of biomedical materials.
Prosthetic Design	30% weight reduction	Specifically observed in pediatric prosthetic knees to improve mobility.
Energy (Fuel Cells)	15% efficiency improvement	Optimized structural and geometric design of solid oxide fuel cells.
Biomedical Repair	35% mechanical strength improvement	Result of hydrogel reinforcement with scaffold composites.
Manufacturing Joints	22% joint strength improvement	Utilizing hybrid polymer–metal staked joint designs.
Mechanical Seals	18% wear rate reduction	Using advanced materials and tribological testing.
System Reliability	27% failure risk reduction	Integration of FEA and DFMEA into the design framework.

3.2 Discussion

This discussion interprets the findings within the frames of mechanical engineering design, where the aspect of relationships

between material properties, failure modes, and selection strategies can be identified.

3.2.1 Material Properties and Failure Mechanisms are interdependent

Based on the results, it is evident that the material properties like strength, ductility and toughness are directly related to the failure behavior. High-ductility materials are most likely to achieve brittle failure whilst ductile materials tend to absorb energy during failure. It is with such interdependence that a balanced approach in the selection of materials is vital.

2.3.2 Importance of Loading and Environmental Conditions

The performance of the material largely depends on loading conditions and environmental factors. Failure is hastened by dynamic loading, high temperatures and corrosive environments. Therefore, the choice of materials should not be dependent on their inherent characteristics, but also on how they can resist the service conditions.

3.2.3 Pros and Cons of Advanced Materials

It has a significant advantage in the form of advanced material, like composite and hybrid, which include reduction in weight and improved mechanical performance. Their intricate failure mechanisms and increased cost are however challenging. Problems like

delamination, interfacial failure, long-term degeneration should be attentively considered in the design and analysis.

3.2.4 The Modern Material Selection Techniques have been effective

Material selection processes have greatly enhanced because of the integration of multi-criteria decision-making methodologies, and calculation tools. Such techniques as FEA and MCDA allow engineers to consider several parameters in addition to each other, which yields more informed and optimized choices. The approaches minimize chances of failure and maximize reliability of systems.

3.2.5 Research Gaps and Future Directions

Despite significant advancements, several research gaps remain. There is a need for more real-world validation of experimental and simulation results. Long-term performance data for advanced materials are limited, particularly under extreme conditions. Additionally, the integration of artificial intelligence and machine learning in material selection is still in its early stages and requires further development.




Fig.17. Future Framework for Intelligent Material Selection Systems

4. Conclusion

The study evaluated the critical relationship between material selection and failure analysis in mechanical engineering. Results established that high-technology materials (composites) enhanced the weight-strength ratio by as much as 40, and hybrid systems enhanced the strength with 22. In addition, studies have shown that the incorporation of predictive analysis such as Finite Element Analysis (FEA), and failure mode analysis minimized the chances of system failure by about 27%. Nevertheless, sophisticated failure modes of anisotropic characteristics, interfacial bond, and severe environmental decay issues were still unresolved engineering problems.

Further studies will consider such weaknesses by experimentally and simulatively industrializing the results with real world conditions and exploring the material degradation under severe thermal and mechanical constraints in the long run. Furthermore, the implementation of AI and machine learning in predictive models

will further streamline the material selection procedure. Adaptive strategies are going to be studied in the future.

Funding

This research received no external funding. The authors conducted this study independently using institutional resources from Hajee Mohammad Danesh Science and Technology University.

Data Availability Statement

The data that support the findings of this study are available from the corresponding author upon reasonable request.

Conflicts of Interest

The authors declare that there is no conflict of interest regarding the publication of this paper.

Reference

- [1]. Miller, B. A. (2021). Materials selection for failure prevention. In *Analysis and Prevention of Component and Equipment Failures* (pp. 3-19). ASM International.
- [2]. Maleque, M. A., & Salit, M. S. (2013). *Materials selection and design*. Springer Singapore.
- [3]. Nishida, S. I. (2014). *Failure analysis in engineering applications*. Elsevier.
- [4]. Makhoul, A. S. H., Herrera, V., & Muñoz, E. (2018). *Handbook of materials failure analysis*. Waltham: Butterworth-Heinemann.
- [5]. Jahan, A., Edwards, K. L., & Bahraminasab, M. (2016). *Multi-criteria decision analysis for supporting the selection of engineering materials in product design*. Butterworth-Heinemann.
- [6]. Afolabi, S. O., & Akinsooto, O. (2021). Theoretical framework for dynamic mechanical analysis in material selection for high-performance engineering applications. *Noûs*, 3(4), 45-62.
- [7]. Adewoyin, M. A., Ogunnowo, E. O., Fiomotonga, J. E., Igunma, T. O., & Adeleke, A. K. (2020). A conceptual framework for dynamic mechanical analysis in high-performance material selection. *IRE Journals*, 4(5), 137-144.
- [8]. Sotoodeh, K. (2018). Analysis and improvement of material selection for process piping system in offshore industry. *American Journal of Mechanical Engineering*, 6(1), 17-26.
- [9]. Ogunnowo, E. O., Adewoyin, M. A., Fiomotonga, J. E., Igunma, T. O., & Adeleke, A. K. (2020). Systematic Review of Non-Destructive Testing Methods for Predictive Failure Analysis in Mechanical Systems. *IRE Journals*, 4(4), 207-215.
- [10]. Ugural, A. C. (2020). *Mechanical engineering design*. CRC Press.
- [11]. Ranjan, R., Rajak, S., & Chatterjee, P. (2023). Material selection for sintered pulley in automobile: An integrated CRITIC-MARCOS model. *Reports in Mechanical Engineering*, 4(1), 225-240.
- [12]. Budynas, R. G., & Nisbett, J. K. (2008). *Shigley's mechanical engineering design* (Vol. 8). New York: McGraw-Hill.
- [13]. Kastratović, G., Grbović, A., Sedmak, A., Božić, Ž., & Sedmak, S. (2021). Composite material selection for aircraft structures based on experimental and numerical evaluation of mechanical properties. *Procedia Structural Integrity*, 31, 127-133.
- [14]. Fragassa, C. (2017). Material selection in machine design: The change of cast iron for improving the high-quality Iin woodworking. *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science*, 231(1), 18-30.
- [15]. Maleque, M. A., & Salit, M. S. (2013). *Mechanical failure of materials*. In *Materials selection and design* (pp. 17-38). Singapore: Springer Singapore.
- [16]. Bingham, K. C., Sourani Yancheshmeh, S., Vaidya, G., Ebrahimpour, A., & Deemyad, T. (2024, November). Advanced material selection and design strategies for optimized robotic systems. In *ASME International Mechanical Engineering Congress and Exposition* (Vol. 88612, p. V003T04A006). American Society of Mechanical Engineers.
- [17]. Ali, M., Ul-Hamid, A., Alhems, L. M., & Saeed, A. (2020). Review of common failures in heat exchangers—Part I: Mechanical and elevated temperature failures. *Engineering Failure Analysis*, 109, 104396.
- [18]. Gagg, C. R. (2014). Cement and concrete as an engineering material: An historic appraisal and case study analysis. *Engineering failure analysis*, 40, 114-140.
- [19]. Juvinall, R. C., & Marshek, K. M. (2019). *Fundamentals of machine component design*. John Wiley & Sons.
- [20]. Dong, L., & Liu, J. (2022). Failure analysis and optimization method research on sealing of deep shale gas ultra-high-pressure fracturing packer rubber. *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science*, 236(19), 10237-10259.
- [21]. Zhao, Y., Deng, X., Shen, M., Bi, J., Wang, C., Zhang, Y., ... & Ning, L. (2026). Analysis of the mechanical properties and failure modes of concrete-sandstone under interface grouting. *Engineering Failure Analysis*, 110820.
- [22]. Jiang, F., Wang, G., He, P., Hou, B., Zhang, S. B., Sun, S. Q., ... & Wu, Y. (2022). Mechanical failure analysis during direct shear of double-joint rock mass. *Bulletin of Engineering Geology and the Environment*, 81(10), 410.
- [23]. Liu, B., Villavicencio, R., & Guedes Soares, C. (2013). Experimental and numerical plastic response and failure of laterally impacted rectangular plates. *Journal of Offshore Mechanics and Arctic Engineering*, 135(4), 041602.
- [24]. Georgantzinos, S. K., Giannopoulos, G. I., Stamoulis, K., & Markolefas, S. (2023). Composites in aerospace and mechanical engineering. *Materials*, 16(22), 7230.
- [25]. Babu, A. R., Sairaju, B., & Amirishetty, S. (2020). Automotive chassis design material selection for road and race vehicles. *Journal of Mechanical Engineering Research and Developments*, 43(3), 274-282.
- [26]. Liu, J., Sun, S., Yue, L., Wei, J., & Wu, J. (2017). Mechanical and failure characteristics of rock-like material with multiple crossed joint sets under uniaxial compression. *Advances in Mechanical Engineering*, 9(7), 1687814017708710.
- [27]. Mohammadzadeh, A., Zadeh, S. K. N., Saidi, M. H., & Sharifzadeh, M. (2020). Mechanical engineering of solid oxide fuel cell systems: geometric design, mechanical configuration, and thermal analysis. In *Design and operation of solid oxide fuel cells* (pp. 85-130). Academic Press.
- [28]. Krishnamoorthy, R. R., Rozani, N., & Marius, D. (2025). Mechanical and stability testing of aerospace materials. In *Aerospace Materials* (pp. 75-101). Elsevier.
- [29]. Mangera, T., Kienhöfer, F., Carlson, K. J., Conning, M., Brown, A., & Govender, G. (2018). Optimal material selection for the construction of a paediatric prosthetic knee. *Proceedings of the Institution of Mechanical Engineers, Part L: Journal of Materials: Design and Applications*, 232(2), 137-147.
- [30]. Huda, Z. (2022). *Mechanical behavior of materials*. Cham: Springer International Publishing.
- [31]. Ahmed, S., & Salehi, S. (2021). Failure mechanisms of the wellbore mechanical barrier systems: Implications for well integrity. *Journal of Energy Resources Technology*, 143(7), 073007.
- [32]. Wang, Yixian, Hui Zhang, Hang Lin, Yanlin Zhao, Xian Li, and Yan Liu. "Mechanical behavior and failure analysis of fracture-filled gneissic granite." *Theoretical and Applied Fracture Mechanics* 108 (2020): 102674.

- [33]. Lei, L., He, X., Yu, T., & Xing, B. (2019). Failure modes of mechanical clinching in metal sheet materials. *Thin-Walled Structures*, 144, 106281.
- [34]. Ogunnowo, E. O., Adewoyin, M. A., Fiomotonga, J. E., Igunma, T. O., & Adeleke, A. K. (2023). A conceptual framework for reliability-centered design of mechanical components using FEA and DFMEA integration. *Journal of Frontiers in Multidisciplinary Research*, 4(1), 342-361.
- [35]. Nau, B. S. (1997). Mechanical seal face materials. *Proceedings of the Institution of Mechanical Engineers, Part J: Journal of Engineering Tribology*, 211(3), 165-183.
- [36]. Abibe, A. B., Amancio-Filho, S. T., Dos Santos, J. F., & Hage Jr, E. (2013). Mechanical and failure behaviour of hybrid polymer–metal staked joints. *Materials & Design* (1980-2015), 46, 338-347.
- [37]. Ashby, M. F., & Johnson, K. (2013). *Materials and design: the art and science of material selection in product design*. Butterworth-Heinemann.
- [38]. Xu, C., Cui, Y., Xue, L., Chen, H., Dong, J., & Zhao, H. (2023). Experimental study on mechanical properties and failure behaviours of new materials for modeling rock bridges. *Journal of Materials Research and Technology*, 23, 1696-1711.
- [39]. Long, R. G., Bürki, A., Zysset, P., Eglin, D., Grijpma, D. W., Blanquer, S. B., ... & Iatridis, J. C. (2016). Mechanical restoration and failure analyses of a hydrogel and scaffold composite strategy for annulus fibrosus repair. *Acta biomaterialia*, 30, 116-125.